



The Difference Is Performance!

DUCE NOZZLE

Tight water pattern for efficient cleaning and pulling



ADVANTAGES

- Unique Vibrating 'Jackhammer' Action
- Replaceable Titanium Ceramic Inserts Included
- Stainless Steel Inserts Only Available for .375" and .25"
- Safer than Cutting and Milling
- Less Chance of Damaging Pipes
- Designed to be Used as a Leach Aid Remover for Landfill

APPLICATIONS

- **SANITARY, STORM**
- Scale Removal
- Mineral Deposits
- Tuberculation
- Concrete and Asphalt

TECHNICAL SPECIFICATIONS

- **DO NOT USE IN CLAY PIPE**
- Nozzle Body Made of Highly Wear-Resistant, Stainless Steel

QUICK FACTS:

- Pipe Range: 2"+
- Flow Range: 5 GPM - 125 GPM
- Pressure Range: 1300 PSI - 2000 PSI
- Hose Sizes: .375" - 1.25"

KEG DUCE NOZZLE

Product Shown Above	Part Number	Hose Size	Number of Inserts	Insert Size	Weight (pounds)	Dimensions	Pipe Size
A	100199-S	.25"	3 Rear 1 Rotating	M5	.4	3.4" x 1.8"	From 2"
B	100105-S	.375"	Factory	M5	.45	1.78" x 1.25"	From 2"
B	100106	.5"	3 Rear 3 Rotating	M8 M6	1.75	3.4" x 1.8"	From 4"
C	100107	.75"	4 Rear 2 Rotating	M8 M6	6.5	5" x 3"	From 4"
D	101108 Duce Small	1"	4 Rear 2 Rotating	M8 M6	6.25	5" x 3"	From 4"
D	101108 Duce Large	1"	4 Rear 2 Rotating	M8 M6	14.4	6.5 x 4"	From 6"
E	101109	1.25"	4 Rear 2 Rotating	M8 M6	13.8	6.5" x 4"	From 6"

The Duce Nozzle is offered with titanium ceramic inserts only except for .25" and .375" nozzles as noted above.