



epoke®




TOWED SPREADERS

epoke is innovation!



The Epoke principle delivers unparalleled precision and accuracy of material delivery.

epoke principle patented 1956




Epoke's Industry-best



**We Build It.
We Back It.**

Epoke equipment is characterized by durability and dependability and the most protective paint process in the industry.



Combined with multi-stage curing treatments and stainless steel fasteners, this process provides optimum anti-corrosion protection, guaranteed for 10 years!

**15 Year
Parts Availability
Guarantee**



*Includes all components and
electronic controls*

EpoMini Series & PSL

EpoMini 5



- Drop Spreader- Minimizes damage to the surrounding landscape
- Uses 1/10th versus using a hand shovel!
- Long Life:
 - Serviceable
 - Parts availability
 - 10 yr rust warranty

Capacity	50 liters	1.8 cubic feet
Total Width	750 mm	29.5"
Track Gauge	700 mm	27.5"
Spreading Width	550 mm	22"
Weight	30 kg	66 lbs

EpoMini 20



- Typical tow tractor:
 - ATV
 - Small garden tractor
- Long Life:
 - Serviceable
 - Parts availability
 - 10 yr rust warranty

Capacity	200 liters	7.1 cubic feet
Total Width	1065 mm	42"
Track Gauge	990 mm	39"
Spreading Width	800 mm	31.5"
Weight	75 kg	165 lbs

PSL 6.5

- 3 Point Hitch Mount
- Self Loading
- Requires 2 tractor hydraulic circuits:
 - Loading
 - Spreader operation

Capacity	600 liters	3/4 cubic yard
Total Width	1980 mm	78"
Spreading Width	1770 mm	70"
Weight	315 kg	695 lbs



PM Series

PM 1.4

PMH 1.4



- 3 Point Hitch Mount
- Hydraulically driven -
2 transmission choices:
 - 30 liter (8 gal)/ minute
 - 15 liter (4 gal)/ minute
- Available hopper extensions:
 - 60 liter (2.0 cubic feet)
 - 140 liter (5.0 cubic feet)
- Not road speed related

Capacity	140 liters	5.0 cubic feet
Total Width	1090 mm	43"
Spreading Width	1010 mm	40"
Weight	85 kg	188 lbs



- 3 Point Hitch Mount
- PTO driven
- Available hopper extensions:
 - 60 liter (2.0 cubic feet)
 - 140 liter (5.0 cubic feet)
- Not road speed related

Capacity	140 liters	5.0 cubic feet
Total Width	1090 mm	43"
Spreading Width	1010 mm	40"
Weight	91 kg	201 lbs



PMW 1.4

- 3 Point Hitch Mount
- Wheel driven
- Road speed related!
- Available hopper extensions:
 - 60 liter (2.0 cubic feet)
 - 140 liter (5.0 cubic feet)

Capacity	140 liters	5.0 cubic feet
Total Width	1140 mm	45"
Spreading Width	1010 mm	40"
Weight	95 kg	210 lbs

ITM 35



- Towed- road speed related
- Contractor Grade
- Optional Drawbars
- Dealer Installed Options:
 - Lights
 - Electric remote
 - Support leg

Capacity	350 liters	½ cubic yard
Total Width	1150 mm	45"
Track Gauge	1030 mm	40.5"
Spreading Width	780 mm	31"
Weight	145 kg	320 lbs

ITM 45



- Towed- road speed related
- Contractor Grade
- Optional Drawbars
- Dealer Installed Options:
 - Lights
 - Electric remote
 - Support leg
 - 250 liter hopper extension

Capacity	450 liters	5/8 cubic yard
Total Width	1435 mm	56.5"
Track Gauge	1290 mm	51"
Spreading Width	1010 mm	40"
Weight	192 kg	423 lbs

ITM 60



Capacity	600 liters	¾ cubic yard
Total Width	1895 mm	75"
Track Gauge	1730 mm	68"
Spreading Width	1460 mm	57.5"
Weight	220 kg	485 lbs

- Towed- road speed related
- Contractor Grade
- Optional Drawbars
- Dealer Installed Options:
 - Lights
 - Electric remote
 - Support leg

SKE Series

SKE 15



- Towed- road speed related
- Municipal Grade
- Optional 0.5 m³ (0.7 cubic yards) hopper extension

Capacity	1.25 m ³	1.64 cubic yard
Total Width	1665 mm	66"
Track Gauge	1000 mm	31"
Spreading Width	1390 mm	55"
Weight	600 kg	1323 lbs

SKE 8



- Towed- road speed related
- Municipal Grade
- Optional Combi Liquid Kit:
 - On new builds or can be retrofit on existing units
 - 360 liter (95 gallon) liquid tanks



Capacity	750 liters	1 cubic yard
Total Width	1285 mm	51"
Track Gauge	790 mm	31"
Spreading Width	1008 mm	40"
Weight	400 kg	880 lbs

SKE 20



- Towed- road speed related
- Municipal Grade

Capacity	1.65 m ³	2.16 cubic yard
Total Width	2195 mm	86"
Track Gauge	1530 mm	60"
Spreading Width	1920 mm	76"
Weight	720 kg	1588 lbs

TK & TMK Series

TKB12-280



- Towed- road speed related
- Municipal Grade
- Spreads when driving forward **and backward**
- Optional hopper empty sensor

Capacity	1.2 m ³	1.6 cubic yard
Total Width	2800 mm	110"
Track Gauge	1800 mm	71"
Spreading Width	2500 mm	98"
Weight	710 kg	1565 lbs

TK12E-260



- Towed- road speed related
- Municipal Grade
- Spreads when driving forward (only)
- Optional hopper empty sensor

Capacity	1.2 m ³	1.6 cubic yard
Total Width	2600 mm	102"
Track Gauge	1500 mm	59"
Spreading Width	2215 mm	87"
Weight	610 kg	1345 lbs

TMK10-275

Capacity	1.0 m ³	1.3 cubic yard
Total Width	2750 mm	108"
Track Gauge	2330 mm	92"
Spreading Width	2000 mm	79"
Weight	400 kg	882 lbs



- Towed- road speed related
- Contractor Grade
- Spreads when driving forward (only)
- Optional hopper empty sensor



THE EPOKE ADVANTAGE

epoke is innovation

From the original spinner disc through ongoing advancements in runway, walkway and road maintenance, Epoke is innovation!

environment

Epoke's advanced control system ensures accurate rates and precise placement of material- reducing environmental impact!

ease of use

Compact size, big results!

endurance

We build it. We Back it! Manufactured to ISO standards with quality components - Epoke spreaders are built to last and backed with an industry best warranty!

economy

From reductions in material use to long life components... save money on materials, save money on your spreader life cycle cost!

Epoke dealers are chosen because of their expertise and commitment to providing superior customer service and solutions. Our dealer program provides comprehensive and ongoing training as well as integrated customer support. Service you can rely on, equipment you can depend on - a team you can trust!

Epoke North America Inc.

2458 Huntley Road,
Stittsville, ON Canada, K2S 1B8



2521 BOWMAN ST
INNISFIL, ONTARIO
L9S 3V6 CANADA
PHONE: 705.733.7700
FAX: 705.733.8800

www.epokena.com