

# 550VX DUAL JETTER SERIES



## FEATURES

- » Power by CAT – unexcelled performance and reliability.
- » Vacuum pump blowers by Gardner Denver – rugged and high performance.
- » Vacuum pump blowers by Gardner Denver – rugged and high performance.
- » 550 gallon spoils tank capacity.
- » 500 gallon fresh water capacity.
- » 400' of ¾" sewer jetter hose» Balanced design with optimum tongue weight – easy on your trucks.
- » Hydraulic powered wind and unwind jetter hose reel.
- » 150 ° articulated jetter hose reel.
- » Significant lower operating cost than larger vacuum and jetting trucks.
- » Compact low profile – good visibility for your driver and stability in rough locations, get into many locations that are nearly impossible with larger vacuum and jetting trucks.
- » Reverse flow is standard – fast tank emptying, blow obstructions out of vacuum hose and back flush the filters for quick-easy cleaning.

## AN IDEAL MACHINE FOR

- » Clean up to 18" lines.
- » Potholing – safely dig test holes in the ground to locate buried utilities for horizontal directional drills.
- » Safe utility locating and/or daylighting.
- » Clean out storm drains, catch basins and valve boxes.
- » Cleaning up drilling fluids and mud.

# 550VX DUAL JETTER SERIES

FEATURES	VL 550
Mountings	Trailer, truck & skid mounting available
Spoils Capacity (gallons / liters)	550 gallons / 2,082 liters
Water Capacity (gallons / liters)	2 x 250 gallons / 2 x 946 liters
Optimum & Balanced Tongue Weight	454 lbs
Engine	81 Hp CAT Turbo Industrial water cooled diesel
Fuel Tank Capacity (gallons / liters)	29 gallons / 110 liters
Premium Silencer Kit w/ Insulated Enclosures and High Performance Silencers	Standard
Warranty	One Year

## CONTROLS LOCATION

Hour Meter / Tachometer / Vacuum Gauge	Standard
Excavator Water Supply Reel	Rear Curbside
Load Level Indicator and Auto Shutoff	Sight Glass and Auto Shutoff
Reverse Flow	Available
Winterize Kit	Standard

## HYDRAULIC HOIST UNLOAD

Hydraulic Hoist Unload	Twin cylinder
Full Opening Rear Door	Hydraulically operated
Rear Door Latch	Single handle, power door lock available
Inlet Valve Size / Drain Valve Size	4" / 6"

## TRAILER DETAILS

Trailer/Hitch Type	Twin Axle Low Profile / Pintle
Height x Length x Width (feet / inches) / (mm)	84" x 22'1" x 95" / 2,133 mm x 6,731 mm x 2,413 mm
Empty Weight - lbs / kg	8,610 lbs / 3,905 kg
Gross Vehicle Weight Rating (lbs / kg)	16,000 lbs / 7,257 kg
Axles, Capacity and Suspension Type	2 x 6,000 lbs Torsion
Tire Size	235/75 R 17.5 Load Range H
Trailer Brakes	Never adjust electric

## VACUUM PUMP / BLOWER DETAILS

Vacuum Pump/Blower Type	Positive displacement lobe pump
CFM / Max Hg	1000 CFM / 15" / Gardner Denver Blower
Max Vac Level - in Hg	15
Reverse Flow	Standard

## WATER SYSTEM DETAILS

Electronic Low Water Shut-Off	Standard
Auto Water Pump Unloader to Reduce Engine Loading & Wear	Standard
Water Pump Drive	Belt w/ Electric Clutch
Water Supply Hose	50' x 3/8" ID
Easy-to-Use Winterize System	Standard

## OPTIONS

Patented Cyclo-Jet Pothole Excavator – Stainless or Dielectric	Available
Curbside Remote Auxiliary Hydraulics	Optional
Full Hydraulic Remote Controlled Boom or Manual Boom	Optional
Lighted Arrow Bar to Direct Traffic	Optional
Removable Water Heater	Optional
4" - 6" Vac Hose Upgrade	Available on HiCFM only
In Tank Clean Out System	Optional
Spin Doctor Valve Exerciser – Mounted with Required Extenders	Optional



1.800.263.1262 | [jjei.com](http://jjei.com) | [info@jjei.com](mailto:info@jjei.com)