

738 TRAILER JET



In this line of work, the pressure to get the job done right is always high.

That's exactly why Spartan designed the 738 trailer-mounted jetter. The 738 gives you all the power and performance you expect at a price you can afford. Serving up 2,000 PSI at 12 GPM, a twin-cylinder, air-cooled engine, plus great Spartan features like automatic lowwater shutoff and rear-mounted operator controls; the 738 has everything you need to meet even the toughest challenges.

SPECS

- Pipe sizes: 3" 12" diameter
- Pressure 2,000 PSI
- · Flow: 12 GPM
- Standard hoses: 250' of 3/8" high-pressure cleaning hose; 100' of 5/8" rubber supply hose
- Weight: 875 lbs empty; 2,200 lbs full
- Size: 120"W x 57"H x 48"D
- Engine: 41.19 cu in (675 cc) twin-cylinder, air-cooled gasoline engine with electric start and solid-state ignition
- · Warranty: (1) year limited warranty



All Spartan trailers are certified fully compliant by the National Association of Trailer Manufacturers.

FEATURES

- Triplex ceramic plunger pump delivers 2,000 PSI @ 12 GPM
- Maneuverable by one person, even with a full water tank
- · Electric start engine
- Rear-mounted operator controls
- Wide-track chassis
- 13" tires with spoke wheels
- 150-gallon water tank
- Automatic low-water shutoff
- Air-purge system protects against cold weather conditions
- Locking toolbox
- 5-position nozzle holder
- 8-gallon fuel tank

SAFETY

- 12" nozzle anti-turn device
- Bright colored 15 ft leader hose

OPTIONAL ITEMS

- · Mobile hose reels for remote operation
- Stainless steel hoses in various lengths for ultraflexible cleaning needs

